Vertica 100





Applications

- PA system
- Clubs & Theatres
- Multi-function hall
- Solo artists, band, DJ
- Education
- Transportation

Description

The Vertica 100 is a passive column speaker part of the Vertica series.

The Vertica cabinets are compact, modular and powerful and the complete serie include two sub units and two column models.

The Vertica 100 uses 12 x 3" (0.75" voice coil) neodymium transducers offering a coverage of 15° +/- 5° V x 100° H and 121dB SPL.

Weight has been left as low as possible providing easy set up in fixed installation as well as easy transport for portable applications.

The Vertica 100 is powered from the sub bass units which include a Digital Signal Processor offering different presets to cover a wide range of sound applications.

Key Feature

- Compact & versatile
- Powered from the sub unit
- DSP presets for wide applications
- Weather proof components
- Easy to use, easy to install
- Portable
- Available in black or white

Specifications

Frequency Range (-10 dB) ¹ :	150 Hz - 20 KHz
Frequency Response (±3dB) ¹ :	180 Hz - 18 KHz
Sensitivity (1w@1m):	96 dB
Nominal Impedance:	8 Ohms
Peak Maximum SPL:	127 dB
Power Rating:	300W / 600W / 1200W
(Continuous ² /Program/Peak)	
Coverage Pattern:	15° ± 5° x 100° (V x H)
Dimension (H x W x D):	1030 x 89 x 116 mm
Net Weight:	13 Kg
HF Driver:	12 x 3" speaker with 0.75" voice coil
Input Connectors:	2 x Neutrik [®] Speakon [®] NL4MP
Enclosure Construction:	1.5 mm stainless steel
	Micro-textured epoxy paint

1.In full-space. 2. IEC Filtered Pink Noise with 6dB Crest Factor, 2 hours duration.