# Horizon 100

# Quad-Amp Column Speaker

12 x 3".



#### •

# **Applications**

- PA system
- Clubs & Theatres
- Public buildings
- Education
- Transportation
- Front Fill / Stage in-fill

# Description

The Horizon 100 is a quad-amp column speaker which consists of 12 x 3" (0.75" voice coil) neodymium transducers. Although it has same out looking with Vertica 100, but the internal structure and character are total different.

Horizon 100 has 100° vertical coverage pattern. For the horizontal angle, it can be changed from 15° to 90° depends on different DSP Preset.

Horizon 100 needs 4 amplifier channels, each amplifier channel need independent DSP processing. All DSP presets are calculated with precise tuning and test. Hence, Horizon 100 is not a normal column speaker, it is an intelligent system.

Horizon 100 can be used with subwoofer together and offer better low frequency response. The cabinet is compact, modular and powerful and can offer 127dB Peak SPL.

#### Key Feature

- Ultra-compact, column loudspeaker.
- Consists of 12 x 3" (0.75" voice coil) neodymium transducers.
- Quad-Amplifier, need independent DSP channel.
- 100° Vertical coverage.
- Variable Horizontal coverage angle, from 15° to 90°.
- DSP preset for different applications.
- Weather proof components.
- Available in black or white.

### **Specifications**

Frequency Range (-10 dB)<sup>1</sup>: 150 Hz - 20 KHz

Frequency Response (±3dB)<sup>1</sup>: 180 Hz - 18 KHz

Sensitivity (1w@1m)2: 96 dB

Nominal Impedance: 8 Ohms

Peak Maximum SPL3: 127 dB @ full power

Power Rating: Quad-Amp: 100W / 200W / 400W

(Continuous<sup>4</sup>/Program/Peak)

Coverage Pattern(V x H): 100° x 15° to 90°

Dimension (H x W x D): 89 x 1000 x 117 mm

Net Weight: 13 Kg

HF Driver: 12 x 3" speaker with 0.75" voice coil

Input Connectors: 2 x Neutrik® Speakon® NL4MP

Enclosure Construction: 1.5 mm stainless steel

Micro-textured epoxy paint

<sup>1.</sup>In full-space.

<sup>2.</sup>With full 12 components.

<sup>3.</sup>Calculated with sensitivity and full power rate at full 12 components, 300W RMS, 600W program, 1200W peak 4.IEC Filtered Pink Noise with 6dB Crest Factor. 2 hours duration.