QX-215AS

ЕЛИЗ



Applications

- Club and Bar Installs
- House of Worship
- Live Sound
- Theatres
- Broadcast
- Multi media spaces

Description

The power to size ratio achieved from this cabinet is quite spectacular. The QX-215AS is an extremely compact, very high power, passive sub-bass cabinet in triple band pass configuration delivering 2000W RMS.

It features dual 15" transducers (4" voice coil) with rubber surround for increased levels of pressure, double spider for improved control and linearity, weather protected cone for outdoor use and ventilated voice coil for improved heat dissipation. The QX-215AS has been designed to be used with the QX-12A and QX-15A to extend the low frequency support.

It is made from premium birch plywood and coated with high resistant water-based black paint, includes integrated handles, rubber feet and top hat insertion point for satellite combination with the QX Serles.

KEY Features

- Ultra-Compact
- Very High Performance 4000W
- Versatile Sound reiforcement
- ARK optimised preset
- White & black colour optional

Specifications

Frequency Range (-10 dB) ¹ :	35 Hz - 200 Hz
Frequency Range (-10 uB).	55 HZ - 200 HZ
Frequency Response (±3dB) ¹ :	40 Hz - 150 Hz
Sensitivity (1w@1m):	98 dB
Nominal Impedance:	4 Ohms
Peak Maximum SPL:	137 dB
Power Rating: (Continuous²/Program/Peak)	2000W / 4000W / 8000W
Coverage Pattern:	360°
Dimension (H x W x D):	644mm x 463mm x 600mm
Net Weight:	59 Kg
LF Driver:	2 x 15", Φ4" voice coil
Input Connectors:	2 x Neutrik® Speakon® NL4MP


1. Calculated based on power rating and sensitivity


2. IEC Filtered Pink Noise with 6dB Crest Factor, 2 hours duration


QX-215AS

Double 15" Passive Subwoofer

Dimension







NO. ENNE 20190408 ver

ENNE Inc. (USA) 650 N San Mateo Drive. San Mateo, California, USA CA 94401

ENNE Inc. (HK) 香港九龙弥敦道345号宏利公积金大厦10楼1001-1003室 Tel (852) 2301 1130 Fax (852) 2301 1299 ENNE Inc. (CN) 广州市番禺区钟村镇钟一村高沙工业区自编3号 Tel (020) 8386 3459 Fax (020) 8386 3550

